




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61F 13/00	A1	(11) International Publication Number: WO 92/10983 (43) International Publication Date: 9 July 1992 (09.07.92)
(21) International Application Number: PCT/GB91/02321 (22) International Filing Date: 24 December 1991 (24.12.91) (30) Priority data: 9028075.1 24 December 1990 (24.12.90) GB (71)(72) Applicant and Inventor: GARDNER, Arthur, Michael, Newsam [GB/GB]; The Priory, Ipplepen, Newton Abbot, Devon TQ12 5RT (GB). (74) Agent: ALLSOP, John, Rowland; Rowland Allsop, 10 London End, Beaconsfield, Bucks HP9 2JH (GB). (81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB, GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), MC (European patent), NL (European patent), SE (European patent), US.		Published <i>With international search report.</i>

(54) Title: BANDAGE**(57) Abstract**

A bandage (100) having a first member (120) of elastic material (14) covered by woven material (150) and a second member of inelastic material (160, 165) with hooked elements (170) which engage the woven material of the first member. The second member may be used to fasten (165) the first member or to provide inelastic regions (160) on the first member for support etc. Slits (180, 185) or apertures (190) may be introduced to the first member to increase the scope of use of the bandage.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT, on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU ⁺	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TC	Togo
DE*	Germany	MC	Monaco	US	United States of America
DK	Denmark				

⁺ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

BANDAGE

This invention relates to bandages. In particular, it relates to a bandage which provides flexibility of use and extended scope of application over bandages presently available.

5

Existing bandages are typically in the form of a strip which is stored in a roll, or in the form of a tube. The tube may be shaped to conform to the particular location at which it is to be used, for example at the ankle joint. A tube, or sleeve, is generally a more convenient form than a strip since it is quick and relatively easy to apply, although its shape and size limit the scope of application.

15 Depending on the circumstances of use, a sleeve, in particular, may suffer the following disadvantages:-

- (i) it may be unduly restrictive to movement in a certain direction in which free movement is preferable;
- 20 (ii) ~~it~~ it may not provide sufficient support, allowing too much movement in a certain direction or directions in which restricted movement is preferable;
- (iii) it may be uncomfortable and, in particular, may not fit adequately;
- 25 (iv) it may tend to kink when the joint is flexed;
or
- (v) it may cover an area which needs to remain open or accessible, such as a wound or bed sore.

30 According to the invention, there is provided a bandage having a first member comprising an elastic layer covered on at least one surface by a woven material, and a second member comprising a base material with upstanding hooked elements, the hooked elements of the second member engaging

35

. -2-

the woven material of the first member; wherein the first member has lines or areas of weakness and the base material of the second member is less elastic than the first member.

5

The first member may be easily extensible and the lines or areas of weakness may be local in extent. Such lines or areas of weakness provide means for controlling the stretching of the first member in diverse local areas and in specific directions according to the requirements of a particular application. Lines or areas of weakness are preferably slits or cuts only partially through the first member, but may be made through the entire thickness of the first member. The lines or areas of weakness may be introduced in situ and/or during manufacture. Lines of weakness are preferably generally parallel to the longitudinal axis of the limb to be bandaged. The bandage may thus be adapted to allow easy movement in specific areas and in specific directions since the first member will stretch in a direction generally normal to each slit. The use of a series of lines of weakness in the form of a lattice allows stretching in all directions.

15
25

In a preferred embodiment, the areas of weakness may be apertures which allow access to a wound site, for example, or which prevent wrinkling of the bandage during flexing of a joint.

30

Preferably, the second member provides means for fastening the bandage when the hooked elements engage with the woven material of the first member. More preferably, one or more pieces of the second member may be used to strengthen the bandage by limiting or preventing stretching of the first member. One or more pieces of the second member may also be used to seal unwanted lines or areas of weakness in the first member.

35

-3-

The elastic layer is preferably of Neoprene or similar material. The woven material is preferably attached to the elastic layer by adhesive, although alternative methods, such as heat sealing for example, may be used.

5

Still more preferably, means for holding inserts in position may be provided. The means may be pockets in the woven material which can hold inserts such as protective pads and plates, or inflatable pads for use with impulse-compression pads for local treatment of joints or tissues or activation of physiological venous pumps, eg. of the hand, foot, calf, knee or thigh.

Alternatively, inserts may be located by positioning the inserts next to the first member and fixing in place by one or more pieces of the second member. In this manner inserts may be located on either side of the first member as required.

20 The bandage is suitably manufactured in the form of a sheet, but preferably it is in the form of a tubular bandage of a particular joint shape. Strips of bandage may be obtained by cutting a sheet into the required length and/or width. Tubular bandages may also be made in situ by sealing the ends of a sheet of the first member with one or more strips of the second member. A sheet may thus be closed by the one or more strips of the second member so as to form a cylinder.

30 The bandage may have an adhesive layer on part or all of at least one surface of the first member. Such an adhesive layer would improve protection of damaged ligaments or structural tissue by adhering to the skin surface.

35

-4-

According to a further aspect of the invention, there is provided a method of manufacturing a bandage comprising: manufacturing a first member by providing a layer of elastic material, attaching a layer of woven material on at least one surface of the layer of elastic material, and cutting slits through part or all of the first member thus formed; providing one or more pieces of a second member which is less elastic than the first member; and fastening the one or more pieces of the second member to the first member by engaging hooked elements on the second member with the woven material of the first member.

Applications of the bandage the subject of the invention include:

- (i) Circumstances where support is required, such as in the protection of damaged ligaments, where appropriately positioned inhibition means can be used;
- (ii) to hold impulse-compression pads inside a tubular bandage for local treatment of joints and tissues;
- (iii) where rapid and unskilled placement of dressings with localised pressure is required, such as for preventing the bleeding of a wound in an emergency;
- (iv) where ventilation of pressure sores or relief of pressure is required; and
- (v) in the construction of an immobilisation cast for body or limb, with the addition of a quick-setting material such as an alginate or plaster of Paris.

The thickness of the bandage is not critical to the invention since it should be suited to the particular material used and the specific application envisaged. A typical useful thickness is from 1.5 mm to 8 mm.

The numbers, sizes, shapes, locations, orientations and degrees of the areas of elastic inhibition and assistance

-5-

govern the shape and characteristics of the bandage so that the bandage can be tailor-made for a specific application. Thus a bandage can be manufactured for application, not only for a particular site, but also
5 for a particular purpose, and applied with speed and ease even by an unskilled person. Likewise, a bandage can be altered or adjusted before or during fitting to suit a special requirement. The bandage should conform to the particular application in that it must not compromise
10 circulation.

The bandage and/or inhibition means may be colour-coded to indicate the degree to which they are elastic.

15 The invention will now be described by way of example with reference to the accompanying drawings, in which:

Fig 1 is a schematic transverse section of a bandage according to the invention;

20

Fig 2 is a schematic plan view of another bandage according to the invention;

Fig 3 is a schematic transverse section of the bandage of Fig 2 viewed in direction A-A;
25

Fig 4 is a schematic plan view of a further bandage according to the invention;

30 Fig 5 is a schematic plan view of a stretched section of the bandage of Fig 4; and

Fig 6 is a schematic side view of a yet further bandage according to the invention.

35

-6-

In Fig 1, there is shown a bandage 10 comprising a first member 20 and a second member 30. The first member 20 has a layer 40 with a covering layer on each side. The covering layer on one side provides a comfort layer 55 for contact with the body and may also be used for location of inflation pads by a further second member. The covering layer 50 on the other side is engaged by hooked elements 70 extending from layer 60 of the second member 30. Layer 40 is an elastic material such as Neoprene with covering layers 50 and 55 being woven material. In use the woven material 50, 55 is attached to the elastic material 40 during manufacture, by adhesive for example, so that the first member 20 can be stretched around the part of the body to be bandaged.

Layer 60 is less elastic than the first member or may be inelastic, being a moulded plastics material for example. In use, the hooked elements 70 engage the woven material 50, preventing stretching of first member 20 at the points of attachment.

Figs 2 and 3 show an embodiment in which a bandage 100 has slits 180, 185 cut in its first member 120, and an aperture 190. Slits 180 are partial thickness, being cut through the woven material 150 only. Slits 185 are full thickness, being cut through both layers of the first member 120, comprising woven material 150 and elastic material 140 only in this embodiment.

Strips of inelastic material 165 are provided for securing the bandage and pieces of inelastic material 160 is placed around the aperture 190 so as to provide a local inelastic region which prevents unwanted deformation of the bandage.

35

-7-

Second member pieces 160, 165 may be Velcro (registered trade mark) or other similar inelastic material having hooked elements. The first member is, for example, wetsuit material, which may be 3 mm Neoprene lined with a 0.5 mm thick woven material. It will be appreciated that other materials could be used. In particular woven material 150 could be a piled fabric, such as plush, or could have looped elements which engage with the hooked elements 170.

10

In use, sheets of bandage 100 are placed around the part of the body to be bandaged and are secured in place by strips of inelastic material 165. Slits 180 in the sheet provide lines of weakening, so that the sheet stretches generally normal to these lines. Instead of being manufactured as a sheet, the bandage may be manufactured in the form of a tube. In this case, slits are provided around arcs of the circumference of inelastic material. Unwanted slits may be sealed by strips of pieces of inelastic material. Further strips of inelastic material may be positioned where extra support or strengthening is required, such as along damaged ligaments or across incompletely healed fractures.

20

This example uses inelastic material for securing or strengthening, but it is possible to use material which is less elastic than that of the first member.

30

In practice, the more preferred form of the bandage 200 would have multiple slits 280 in a "bricked" layout, as shown in Fig 4. These slits 280 deform when stretched around a limb during application as shown in Fig 5. The multiple slits become a lattice of diamond shapes 285 when stretched as indicated by the arrows. The use of this form enables stretching in all directions. Improved stretching is thereby achieved over the whole of the lattice region.

35

-8-

The bandage 200 may be closed by a longitudinal strip of the second member 265 to form a tubular bandage.

5 The slits are generally closely spaced along the longitudinal axis of the limb to be supported. This weakens the force exerted by the first member so that by itself it exerts only minor constricting force to the limb.

10 Fig 6 shows an embodiment in which the bandage has been manufactured in the form of a tubular support bandage 300 and shaped to conform to a knee joint. Slits 380 have been cut in the region where stretching of the bandage is required and have deformed to a diamond lattice. Further support to ligaments, for instance, is provided
15 in the form of inelastic or less elastic regions obtained by the addition of strips of the second member 330. If necessary, an aperture 390 can prevent wrinkling of the bandage, the aperture being maintained in shape by a piece of the second member 360. The strips 330
20 may also be used to close a slit 380 if it is not required.

A versatile bandage and method of manufacturing a bandage have thus been provided which provide quick and easy application without the requirement of a large range
25 of custom-fit bandages. It will of course be understood that the present invention has been described purely by way of example, and modifications can be made within the scope of the invention.

30

35

-9-

CLAIMS

1. A bandage having a first member comprising an elastic layer covered on at least one surface by a woven material, and a second member comprising a base material with upstanding hooked elements, the hooked elements of the second member engaging the woven material of the first member; wherein the first member has lines or areas of weakness and the base material of the second member is less elastic than the first member.
2. A bandage according to claim 1, in which the lines or areas of weakness are slits through part or all of the first member.
3. A bandage according to claim 1 or claim 2, in which the areas of weakness are apertures.
4. A bandage according to any one of claims 1 to 3, in which the second member provides means for fastening the bandage.
5. A bandage according to any one of claims 1 to 4, in which the second member provides means for strengthening the bandage.
6. A bandage according to any one of claims 1 to 5, in which the elastic layer is Neoprene or similar material.
7. A bandage according to any one of claims 1 to 6, in which the woven material is attached to the elastic layer by adhesive.
8. A bandage according to any one of claims 1 to 7, in which the bandage further includes means for containing inserts.

-10-

9. A bandage according to any one of claims 1 to 8, in which the first member is in the form of a strip, sheet or tube.

5 10. A bandage according to any one of claims 1 to 9, in which the first member further comprises an adhesive layer on part or all of at least one surface.

10 11. A method of manufacturing a bandage comprising:
manufacturing a first member by providing a layer of elastic material, attaching a layer of woven material on at least one surface of the layer of elastic material, and cutting slits through part or all of the first member thus formed;

15 providing one or more pieces of a second member which is less elastic than the first member; and
fastening the one or more pieces of the second member to the first member by engaging hooked elements on the second member with the woven material of the
20 first member.

12. A bandage substantially as hereinbefore described with reference to Fig 1, or Figs 2 and 3, or to Fig 4 of the drawings.

25 13. A method of manufacturing a bandage substantially as hereinbefore described.

30

35

1/2




Fig. 1.




Fig. 2.







Fig. 3.

SUBSTITUTE SHEET

2/2

*Fig. 4.**Fig. 5.**Fig. 6.***SUBSTITUTE SHEET**

INTERNATIONAL SEARCH REPORT

PCT/GB 91/02321

International Application No

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all)⁶

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 A61F13/00

II. FIELDS SEARCHED

Minimum Documentation Searched⁷

Classification Systems

Classification Symbols

Int.Cl. 5

A61F

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched⁸III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹

Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
Y	US,A,2 096 564 (W.M.SCHOLL) 19 October 1937 see the whole document ---	1-4,6-7, 9-13
Y	US,A,4 926 848 (J.W.SHIMKUS AND J.M.BROWNELL) 22 May 1990 see abstract see column 3, line 33 - line 48 see column 4, line 35 - line 38 see column 5, line 54 - line 56; figures ---	1-4,6-7, 9-13
A	US,A,4 926 846 (L.G.NASSAR) 22 May 1990 see column 2, line 21 - line 32 see column 3, line 47 - line 52; figures 1,5 ---	6
A	FR,A,2 166 764 (T.NAKAYAMA) 17 August 1973 see page 3, line 14 - page 4, line 17; figures 1-2 ---	5,8

¹⁰ Special categories of cited documents:^{"A"} document defining the general state of the art which is not considered to be of particular relevance^{"E"} earlier document but published on or after the international filing date^{"L"} document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)^{"O"} document referring to an oral disclosure, use, exhibition or other means^{"P"} document published prior to the international filing date but later than the priority date claimed^{"T"} later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention^{"X"} document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step^{"Y"} document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.^{"A"} document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

09 APRIL 1992

Date of Mailing of this International Search Report

22 APR 1992¹

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

NICE P.

P.R. Nice

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)

Category ^a	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
A	FR,A,2 533 434 (F.J.BONNER JR. AND F.J.BONNER III) 30 March 1984 see page 8, line 1 - line 27; figure 9 ---	1,4,6,9, 11-13

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. GB 9102321
SA 54826**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 09/04/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-2096564		None	
US-A-4926848	22-05-90	None	
US-A-4926846	22-05-90	None	
FR-A-2166764	17-08-73	None	
FR-A-2533434	30-03-84	US-A- 4534354	13-08-85
		AU-A- 1961683	05-04-84
		CA-A- 1208512	29-07-86
		DE-A- 3334929	29-03-84
		GB-A, B 2127697	18-04-84
		JP-A- 59146657	22-08-84
		SE-A- 8305320	30-03-84

EPO FORM P079

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

1/2




Fig. 1.




Fig. 2.




Fig. 3.

SUBSTITUTE SHEET

2/2




Fig. 4.




Fig. 5.




Fig. 6.

SUBSTITUTE SHEET